

協承昌股份有限公司 JETCOAT CORPORATION 桃園縣 328 觀音工業區榮工南路 15 號/NO.15, Rong-Kong South Road, Guan-Inn Industrial District, Tau-Yuan, 328, Taiwan 電話/TEL:+886-3-4832953 傳真/FAX:+886-3-4832957

Product Code	Product Name	Curing Rate/ Speed 🔆	Application Machine	Features	Usages
JO-200DW	Primer Coat White Ink	8,000PCS/HR (UV Lamp x 2)	 ☑ Øffset Printing. ☑ Rotary Letterpress Printing. ☑ Intermittent Letterpress Printing. 	♦High opacity. ♦Excellent adhesion.	PAPER
JO-220UW	Top Coat White Ink				Pretreated PE, PP, PC and other Plastics
JH-2000Y	UV Ink	8,000PCS/HR (UV Lamp x 2)		 ♦UV energy saving. ♦Fast cure. ♦High color density. ♦Excellent gloss. 	PAPER
JH-2000M	UV Ink				PVC Films, Synthetic Paper, Pretreated PE, PP, PET and other Plastics.
JH-2000C	UV Ink				
JH-2000K	UV Ink				
JO-818Y	UV Ink	8,000PCS/HR (UV Lamp x 2)		 ♦Fast cure. ♦High color density. ♦Excellent gloss. 	PVC Films, Synthetic Paper, Pretreated PE, PP, PET and other Plastics.
JO-818M	UV Ink				
JO-818C	UV Ink				
JO-818K	UV Ink				
JL-05X	Matt Ink Duct	8,000PCS/HR (UV Lamp x 2)		Rotary & Intermittent Letterpress Printing. It gives a well matte performance on surface and good adhesion on paper.	PVC Films, Synthetic Paper, Pretreated PE, PP, PET and other Plastics.
JO-06X	Orange Peel Effect Ink			 ♦ Applying with P-208JN ♦ Excellent Orange Peel Effect 	
JO-08	Primer			\diamond Increases the adhesiveness of UV Offset inks.	
JO-12	Protective Varnish for Ink Duct			 ♦ High Rub resistance/ High scratches resistance. ♦ Excellent Adhesion. 	

*The adjustment is necessary due to different conditions.