



協承昌股份有限公司 JETCOAT CORPORATION

桃園縣 328 觀音工業區榮工南路 15 號／NO.15, Rong-Kong South Road, Guan-Inn Industrial District, Tau-Yuan, 328, Taiwan

電話／TEL：+886-3-4832953

傳真／FAX：+886-3-4832957

Label Over Print Products

products	Viscosity (25°C)	Appearance	Features	Curing Rate (80 watt/in Mercury lamp)	Applied machinery	Package
P-531J	80~100 cP	Clear, pale-yellow liq	● High gloss ● Excellent leveling ● Low yellowing	40 m/min	● Roller coater ● Flexographic printer	20kg/tin can
P-531N	80~100 cP	Clear, pale-yellow liq	● for general can ribbon ● High gloss ● Excellent leveling ● Low yellowing	40 m/min	● Roller coater ● Flexographic printer	20kg/tin can
P-533J	320~380cP	Clear, pale-yellow liq	● High gloss ● Excellent leveling ● Low yellowing	40 m/min	● Roller coater ● Flexographic printer	20kg/tin can
P-508J	250~310cP	Clear liq	● For outside food package ● High gloss ● Excellent leveling ● Low yellowing & low odor	40 m/min	● Roller coater ● Flexographic printer	20kg/tin can
PA-1510	500~600cP	Clear, pale-yellow liq	● Low yellowing ● Simple operation ● Good adhesion for BOPP and PP film	40 m/min	● Roller coater ● Flexographic printer	20kg/platic pail